

Club Car

CARRYALL 232

UTILITY VEHICLES





CARRYALL 232

UTILITY VEHICLES

PERFORMANCE FEATURES

- Lightweight, rust-proof aluminum frame
- Smooth riding front and rear suspension
- Tightest turning diameter in class (5.3 m / 17.4 ft)
- Greater operating range (26.5 L / 7 gal fuel tank)
- Self-adjusting rack and pinion steering
- Choice of gas or electric powertrain

- Self-adjusting rear mechanical drum brakes with foot-operated park brake
- Generous 0.2 m³/7.1 ft³, 136.1 kg / 300 lb bed box capacity
- 362.9 kg / 800 lb total vehicle capacity
- 2 year, 2000 hour limited warranty

- Durable, corrosion-resistant, composite bed box
- Spacious floor-mat covered foot well
- Scratch and impact resistant ABS Plastic front and ArmorFlex[®] rear body
- Available in red or green

- ✓ = Standard Equipment
 ○ = Optional Field-installed Equipment



STANDARD EQUIPMENT

Gasoline Engine
Electric Motor
Reverse Warning Indicator
Headlights
3-cup Beverage Holder
Fuel Gauge/Hour Meter/Oil Light
State of Charge Indicator/Battery Light
Front Impact Protection
12-volt Accessory Plug
Wheels
Dash Storage
Differential Guard

ELECTRIC

NA
48-volt, 10 hp intermittent
✓
✓
✓
NA
✓
Cast Steel Bumper
○
Gray Steel Rims
Dash Pocket
○

GASOLINE

Kawasaki 9.5 hp, 286cc
NA
✓
✓
✓
✓
NA
Cast Steel Bumper
○
Gray Steel Rims
Dash Pocket
○

SPECIFICATIONS

Maximum Speed	27.4-30.6 kph (17-19 mph)	27.4-30.6 kph (17-19 mph)
Vehicle Dimensions (l x w x h)	255.3 x 125.7 x 121.9 cm (100.5 x 49.5 x 48 in.)	255.3 x 125.7 x 121.9 cm (100.5 x 49.5 x 48 in.)
Curb Weight (less battery and fuel)	396.4 kg (874 lb.)	354.3 kg (781 lb.)
Wheelbase	165.1 cm (65 in.)	165.1 cm (65 in.)
Ground clearance under differential	14.0 cm (5.5 in.)	14.0 cm (5.5 in.)
Cargo box dimensions (l x w x h)	65.3 x 110.5 x 27.9 cm (25.7 x 43.5 x 11 in.)	65.3 x 110.5 x 27.9 cm (25.7 x 43.5 x 11 in.)
Tread (front/rear)	86.4/96.5 cm (34/38 in.)	86.4/96.5 cm (34/38 in.)
Tires	20 x 1000 - 8, 4-ply rated, All-trail II	20 x 1000 - 8, 4-ply rated, All-trail II
Front Suspension	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks
Rear Suspension	Leaf springs w/ dual hydraulic shocks	Leaf springs w/ dual hydraulic shocks

ACCESSORIES



Split Windshield and Canopy



Brush Guard



Nerf Bars



Sport Wheel Covers



Taillights



Trailer Hitch & Ball



Locking Glove Box

Club Car

1-800-Club Car • www.clubcar.com

There are no warranties, expressed or implied, contained herein. See Limited Warranty found in the owner's manual or write to Club Car, Inc. The company reserves the right to make design changes without obligation to make these changes on units previously sold. These vehicles are designed and manufactured for off-road use only. They do not conform to Federal Motor Vehicle Safety Standards for automobiles or to FMVSS 500 for low-speed vehicles, and are not equipped for operation on public streets, roads, or highways.

CCN 58644675 Rev 11/09