CARRYALL LI/ION

The Carryall family of vehicles with the Club Car quality you know, **NOW POWERED BY LITHIUM-ION.**

Every day is different. You need a vehicle you can trust to get any job done, even the unexpected ones, without the noise of a gas engine.

THE ADDED BENEFITS OF CARRYALL LITHIUM-ION INCLUDE:

MAINTENANCE FREE BATTERY

The Li-Ion battery eliminates the need for any servicing or battery maintenance of any kind. No more battery watering or terminal cleaning!

LONGER BATTERY LIFE

Designed for the long haul, the Carryall Lithium vehicles come with a 5-year limited battery warranty for peace of mind for your fleet.

MORE EFFICIENT CHARGING

Time is money and Utility Lithium models charge up to 40% faster than lead-acid models.

INCREASED POWER AND PERFORMANCE

Club Car

With enhanced power for hill climb and towing, and a new top speed setting of 19 mph, Carryall Lithium vehicles will help you work more efficiently.

Accomplish more in less time with Zero-Maintenance Lithium Power, now available in Carryall utility vehicles.







CARRYALL LITHIUM

CARRYALL LI/ION

	500	502	550	700
ENGINE	48-volt 3-phase AC	48-volt 3-phase AC	48-volt 3-phase AC	48-volt 3-phase AC
HORSEPOWER	7.4 hp (5.5 kW) rated @ 2863 rpm; Peak 21.4 hp (16 kW)	7.4 hp (5.5 kW) rated @ 2863 rpm; Peak 21.4 hp (16 kW)	7.4 hp (5.5 kW) rated @ 2863 rpm; Peak 21.4 hp (16 kW)	7.4 hp (5.5 kW) rated @ 2863 rpm; Peak 21.4 hp (16 kW)
BATTERIES	Std: Vanguard 7.0kWh Lithium Opt: Vanguard 4.0kWh Lithium	Std: Vanguard 7.0kWh Lithium Opt: Vanguard 4.0kWh Lithium	Std: Vanguard 7.0kWh Lithium Opt: Vanguard 4.0kWh Lithium	Std: Vanguard 7.0kWh Lithium
CHARGER	Std: DeltaQ IC650 - 650W high frequency Opt: DeltaQ IC900 - 900W high frequency	Std: DeltaQ IC650 - 650W high frequency Opt: DeltaQ IC900 - 900W high frequency	Std: DeltaQ IC650 - 650W high frequency Opt: DeltaQ IC900 - 900W high frequency	Std: DeltaQ IC650 - 650W high frequency Opt: DeltaQ IC900 - 900W high frequency
STEERING	Self-adjusting Rack and Pinion	Self-adjusting Rack and Pinion	Self-adjusting Rack and Pinion	Self-adjusting Rack and Pinion
FRONT SUSPENSION	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks
BRAKES	4-wheel Mechanical Drum	4-wheel Mechanical Drum	4-wheel Mechanical Drum	4-wheel Mechanical Drum
PARK BRAKE	Foot operated, multi-lock	Foot operated, multi-lock	Foot Operated, multi-lock	Foot Operated, multi-lock
BODY & FINISH	ArmorFlex™ with automotive paint/clearcoat, aluminum finish	ArmorFlex [™] with automotive paint/clearcoat, aluminum finish	ArmorFlex® with automotive paint/clearcoat, aluminum finish	ArmorFlex® with automotive paint/clearcoat, aluminum finish
TIRES	20 x 10-10, 6-ply, premium tread	18 x 8.5-8, 6-ply, premium tread	22x10-10, 4-ply, extra traction	20 x 10-10, 6-ply, premium tread
BED L X W X H	44.2 x 47.5 x 10.5 in (112.2 x 120.6 x 26.6 cm)	44.2 x 47.5 x 10.5 in (112.2 x 120.6 x 26.6 cm)	44.2 x 47.5 x 10.5 in (112.2 x 120.6 x 26.6 cm)	64.5 x 47.5 x 10.5 in (163.8 x 120.6 x 26.6cm)
WHEELBASE	78.1 in (198 cm)	78.1 in (198 cm)	78.1 in (198.3 cm)	99.1 in (251.7 cm)
GROUND CLEARANCE	5.6 in (14.2 cm)	4.2 in (10.7 cm)	6.0 in (15.2 cm)	5.6 in (14.2 cm)
VEHICLE RATED CAPACITY	1200 lb (544 kg)	1200 lb (544 kg)	900 lb (408 kg)	1500 lb (680 kg)
CARGO BED CAPACITY	800 lb (363 kg)	800 lb (363 kg)	500 lb (227 kg)	1000 lb (454 kg)
CURB WEIGHT	951 lb (431.4 kg)	938 lb (425.5 kg)	1020 lb (462.6 kg)	1013 lb (459.4 kg)
SPEED RANGE	5-19 mph (8-31 kph)	5-19 mph (8-31 kph)	5-19 mph (8-31 kph)	5-19 mph (8-31 kph)
LIMITED WARRANTY	5-year limited battery warranty; 3-year limited powertrain/frame; 2-year limited remaining vehicle	5-yea r limited battery warranty; 3-year limited powertrain/frame; 2-year limited remaining vehicle	5-year limited battery warranty; 3-year limited powertrain/frame; 2-year limited remaining vehicle	5-year limited battery warranty; 3-year limited powertrain/frame; 2-year limited remaining vehicle

Club Car

CARRYALL LITHIUM